

HiStone

Mobile POS System | Tablet | HM626R

Key Features

- ❑ Embedded CPU with high-performance and lower power consumption
- ❑ Bezel-free, PCAP multi-touch 10.1" widescreen display optimizing viewing
- ❑ Optional integrated 1D or 2D barcode scanner and 4G functionality
- ❑ Optional smart docking station with various I/O ports, with or without an optional integrated printer
- ❑ Flexible operational scenarios; mobile, desktop or wall mount



MODEL		HM626R	
Processor		ARM RK3288 (4core) 1.6GHz	
		ARM RK3288 (4core) 1.8GHz	
Operating System		Android 7.1	
Memory		2GB	4GB
Storage		16GB eMMC	64GB eMMC
Display Panel		10.1" TFT LCD (LED backlight) widescreen Standard Resolution 1280 x 800	
Touch Screen		True Flat Capacitive Touch Screen 10 Point Touch	
Power Supply		12V 2A	
Battery		3.8V 11000mAh	
Speaker		2 x 1W	
Buttons		Power, Volume +/-, Barcode Scanner	
I/O Ports	USB	1* 2.0, 1* Micro	
	Audio	1* 3.5mm	
	HDMI	1* Micro	
	Power Out	1* 12V 2A	
	SIM Card	1* Nano	
	TF Card	1* Standard up to 32GB	
Default Peripherals	Wi-Fi®	Dual-band 802.11a/b/g/n/ac 2.4GHz/5GHz	
	Bluetooth	BT 4.1	
	Camera	5MP AF rear-facing	
		2MP AF front-facing	
	MSR	3 tracks MSR	
	GPS	Standard GPS	
	G-sensor	Standard G-sensor	
	Hand Strap	1* Sturdy hand strap	
Optional Peripherals	Charging Dock	1* Charging docking station	
	Encrypted MSR	Magtek Encrypted MSR	
	RFID	3 tracks MSR & RFID (OPOS)	
	Scanner	1D Barcode scanner	
		2D Barcode scanner	
	Connectivity	4G Module	
	Wall Mount	VESA Wall mount bracket	
	Mobility	Shoulder strap	
	Smart Dock	Smart Docking Station with or without integrated 58mm thermal printer	

Disclaimer: All products specifications are subject to change without notice.

MODEL		HM626R
Dimensions (WxDxH)	Tablet	282 x 198 x 18 mm
	Charging Dock	151 x 92 x 121 mm
	Smart Dock	236 x 218 x 150-370 mm
Weight	Tablet	1kg
	Charging Dock	325g
	Smart Dock	2.82kg
Environment	Operating	5°C - 40°C / 40%-90% RH non-condensing
	Storage	-20°C - 60°C/10%-90% RH non-condensing
EMC and Safety		FCC / CE / RoHS
Colour		Black
Charging Docking Station	Power Supply	12V 2A
	I/O Ports	2* USB 2.0
Smart Docking Station	Power Supply	24V 90W
	I/O Ports	3* USB 2.0
		2* RS232 Serial
		1* RJ45 100M LAN Ethernet
		1* RJ11 (D-24V) Cash Drawer
	Optional Peripheral	Integrated 58mm thermal printer
		MPOS Bracket
	Tilt Adjustment	Top Hinge 0° - 180°
		Bottom Hinge 0° - 75°

Disclaimer: All products specifications are subject to change without notice.





- ❑ Default Peripherals include:
Hand Strap, Camera, MSR (3 track), Wi-Fi and Bluetooth
- ❑ Optional Peripherals include:
Integrated Scanner (1D or 2D),
Integrated Encrypted MSR, RFID
& MSR, 4G Module, Shoulder
Strap and Wall Mount Bracket

- ❑ Optional Smart Docking
Station with or without
58mm Integrated Printer



- ❑ The Optional Smart
Docking Station is
equipped with multiple
I/O ports including a LAN
Ethernet Port