

Monitor | MD15HW

Key Features

- ☐ 15.6-inch widescreen monitor, thin and sleek appearance
- ☐ True Flat Capacitive touch layer or non-touch version;
- ☐ Lower Power Consumption;



MODEL	MD15HW
Case/Bezel Color	Black/White
Display Ratio	16:9
Screen Type	15.6 inch TFT-LCD
Backlight Type	LED
Active Display Area	344.16mm(H) × 193.59mm(V)
Native Resolution	1920*1080
Pixel Response Time	30ms
Colors	16.7M
Luminance	250nits
Contrast Ratio	800
Viewing Angle(cr≥10)	Horizontal:170°(85°/85°); Vertical: 170°(85°/85°)
Pixel arrangement	RGB Vertical stripe
Backlight Lamp Life	15000 (Hours To 1/2 Brightness)
Touch Technology	Projected Capacitive Touch (P-Cap)
Active Touch Area	350.66mm (H) × 205.84mm (V)
Light Transmission	≥85%
Surface Hardness	≥7H
Touch Screen Interface	USB
Glass Type	Tempered
Mounting Options	VESA : 75x75mm
Outline Dimensions(mm)	377*226*40 (no base)/ 377 *291*190(with base)
Weight	1.5kg (no base)/ 2.7kg(with base)
Power Supply	External Adapter: 100-240 VAC, 50-60 Hz Input Voltage Range: +12VDC ± 5% ; 40W
On Screen Display (OSD)	Control(back): Power, Auto, Up, Down, Menu
Power Consumption	≤40W
Speaker	1X 3W
IO Ports	1*USB-B
	1* 12V power-in
	1*HDMI
Operating Environment	0°C - 40°C/Humidity: 40%-90% RH non-condensing
Storage Environment	-20°C - 60°C; Humidity: 10% to 90% (Non-condensing)
Input Video Signal Connector	HDMI
EMC & Safety	CE/FCC/ROHS



- 15.6" screen with bezel free design

- Cable cover for better cable management



Disclaimer: All products specifications are subject to change without notice.