

Monitor | MD15VC

Key Features

- ❑ Durable 15" POS monitor with ultra stable base;
- ❑ True Flat Capacitive touch layer or non-touch version;
- ❑ Optional MSR card reader more suitable as POS peripherals;
- ❑ Lower Power Consumption;



MODEL	MD15VC
Case/Bezel Color	Dark gray
Display Ratio	4:3
Backlight Type	LED
Active Display Area	304.128mm(H) × 228.096mm(V)
Native Resolution	1024*768
Pixel Response Time	16ms
Colors	16.7M
Luminance	350nits
Contrast Ratio	1000:01:00
Viewing Angle(cr≥10)	Horizontal:178°(89°/89°); Vertical: 178°(89°/89°)
Input Video Format	RGB Analog
Backlight Lamp Life	50000 (Hours To 1/2 Brightness)
Touch Technology	Projected Capacitive Touch (P-Cap)
Active Touch Area	305.1mm (H) × 229.1mm (V)
Glass Thickness	2.4±0.3mm
Light Transmission	≥85%
Surface Hardness	≥7H
Touch Screen Interface	USB
Glass Type	Tempered
	Anti-Glare (Optional)
Mounting Options	VESA : 75x75mm
Outline Dimensions	360*200*350mm
Power Supply	External Adapter: 100-240 VAC, 50-60 Hz Input Voltage Range: +12VDC ± 5%
On Screen Display (OSD)	Control(back): Power, Auto, Up, Down, Menu
Power Consumption	≤18W
Speaker	null
IO Ports	1*USB-B(option for Touch)
	1* Audio
	1*VGA
Optional Peripherals	Single MSR
	Multi-function MSR: MSR+ RFID+ IC
Operating Environment	0℃ - 40℃/Humidity: 10%-85% RH non-condensing
Storage Environment	-20℃ - 60℃; Humidity: 10% to 85% (Non-condensing)
Input Video Signal Connector	VGA
Operating Altitude	≤3000m
EMC & Safety	CE/FCC/ROHS



- ❑ 15" screen with bezel free design
- ❑ Optional card reader

- ❑ Flexible hinge for better experience



Disclaimer: All products specifications are subject to change without notice.